

Wennington Road, Southport PR9 7TN. England
Tel: 01704 518000 Fax: 01704 518001
WEB SITE http://www.unipartdorman.co.uk
E MAIL address – dorman.info@unipartdorman.co.uk

Health and safety

Every effort has been made to ensure the accuracy of the information given in our publications, but in accordance with our policy of continually improving our products we reserve the right to modify designs and specifications whenever necessary. All equipment is designed to conform to relevant British and International standards. Every care is taken to ensure that, as far as reasonably practical, it will perform without risk to health. It is essential that accepted codes of professional practice are followed in the assembly, installation and commissioning of the equipment. If in doubt with respect to any of these instructions, please consult Dorman before installing the device.

Dorman reserves the right to vary any component part to meet the required specifications without prior notice.



Dorman ref. No C64.65052 Iss 1

MK3 Tail Lamp White (Angolan) Instruction Sheet

STEADY

Installation Instructions

To be read before commencing



Operation









Operating instructions

- Rotate the switch at the rear of the lamp to "ON".
- The Lamp illuminates.
- Side indicator lamps illuminate which indicate that the batteries will operate for a minimum of 12 hours.

Low Battery Indication

If the battery voltage falls below the pre-set limit:


- The lamp will remain on automatically (regardless of ON/OFF switch position).
- The side indicator lights will extinguish.
- The batteries should be changed immediately. Only use AIR ALKALINE batteries as replacements. See replacement parts for order code.

Battery Replacement

To replace the batteries, first remove the retaining bolt from the rear of unit through the access hole in the clamp (if fitted). Tools required – 4mm A/F allen key.



Remove the battery carrier. Release the batteries from their location ledge. Visually inspect the battery contact strips, clean the battery contact strips if necessary. Install two new batteries and replace the battery carrier. Secure with the bolt previously removed. There are no serviceable parts in the lamp to keep maintenance to an absolute minimum



Cleaning

The front lens, reflective panel and the side indicators should be kept clean by wiping with soapy water regularly.

Specification

Light colour:- BS 1376:1974 Signal White

Class C

Switch type:- Optical
Nominal supply voltage:- 6V DC
Nominal current drawn:- 0.049Amps

Replacement Parts.

<u>Description</u>	Dorman Pt No	Pads No
AIR ALKALINE BATTERIES DAAB 50	B13.12170	·
Battery carrier bolt	B17.16146	
Battery Carrier	B05.04018	
Bracket kit incl. fasteners	D29.28010	017/070023
		or
		55/39690
Reflective label	Contact Dorman for pa	rt No.

